## **Ambient Air Quality Standards**

| Pollutant                                     | Averaging<br>Time         | California Standards <sup>1</sup>  |   | Federal Standards <sup>2</sup>     |                                   |  |
|---|---------------------------|--|---|------------------------------------|-----------------------------------|--|
|   |                           | Concentration <sup>3</sup>   | Method <sup>4</sup>   | Primary <sup>3,5</sup>             | Secondary <sup>3,6</sup>          | Method <sup>7</sup>                                |
| Ozone (O <sub>3</sub> )                       | 1 Hour                    | 0.09 ppm (180 μg/m <sup>3</sup> )  | Ultraviolet<br>Photometry   | _                                  | Same as<br>Primary Standard       | Ultraviolet<br>Photometry                          |
|   | 8 Hour                    | 0.070 ppm (137 μg/m <sup>3</sup> )   |   | 0.08 ppm (157 μg/m³) <sup>8</sup>  |                                   |  |
| Respirable<br>Particulate<br>Matter<br>(PM10) | 24 Hour                   | 50 μg/m³   | Gravimetric or<br>Beta Attenuation  | 150 μg/m³                          | Same as<br>Primary Standard       | Inertial Separation<br>and Gravimetric<br>Analysis |
|   | Annual<br>Arithmetic Mean | 20 μg/m³   |   | 50 μg/m <sup>3</sup>               |                                   |  |
| Fine<br>Particulate<br>Matter<br>(PM2.5)      | 24 Hour                   | No Separate State Standard   |   | 65 μg/m³                           | Same as                           | Inertial Separation                                |
|   | Annual<br>Arithmetic Mean | 12 μg/m³   | Gravimetric or<br>Beta Attenuation  | 15 μg/m³                           | Primary Standard                  | and Gravimetric<br>Analysis                        |
| Carbon<br>Monoxide<br>(CO)                    | 8 Hour                    | 9.0 ppm (10mg/m <sup>3</sup> )   | Non-Dispersive<br>Infrared Photometry<br>(NDIR)                               | 9 ppm (10 mg/m <sup>3</sup> )      | - None                            | Non-Dispersive<br>Infrared Photometry<br>(NDIR)    |
|   | 1 Hour                    | 20 ppm (23 mg/m <sup>3</sup> )   |   | 35 ppm (40 mg/m <sup>3</sup> )     |                                   |  |
|   | 8 Hour<br>(Lake Tahoe)    | 6 ppm (7 mg/m <sup>3</sup> )   |   | _                                  | _                                 | _  |
| Nitrogen<br>Dioxide<br>(NO <sub>2</sub> )     | Annual<br>Arithmetic Mean | _  | Gas Phase<br>Chemiluminescence  | 0.053 ppm (100 μg/m <sup>3</sup> ) | Same as<br>Primary Standard       | Gas Phase<br>Chemiluminescence                     |
|   | 1 Hour                    | 0.25 ppm (470 μg/m <sup>3</sup> )  |   | _                                  |                                   |  |
| Sulfur<br>Dioxide<br>(SO <sub>2</sub> )       | Annual<br>Arithmetic Mean | _  | Ultraviolet<br>Fluorescence   | 0.030 ppm (80 μg/m <sup>3</sup> )  | _<br>_                            | Spectrophotometry<br>(Pararosaniline<br>Method)    |
|   | 24 Hour                   | 0.04 ppm (105 μg/m <sup>3</sup> )  |   | 0.14 ppm (365 μg/m <sup>3</sup> )  |                                   |  |
|   | 3 Hour                    | _  |   | _                                  | 0.5 ppm (1300 μg/m <sup>3</sup> ) |  |
|   | 1 Hour                    | 0.25 ppm (655 μg/m³)   |   | _                                  | _                                 | _  |
| Lead <sup>9</sup>                             | 30 Day Average            | 1.5 μg/m <sup>3</sup>  | Atomic Absorption   | _                                  | _                                 | _  |
|   | Calendar Quarter          | _  |   | 1.5 μg/m³                          | Same as<br>Primary Standard       | High Volume<br>Sampler and Atomic<br>Absorption    |
| Visibility<br>Reducing<br>Particles           | 8 Hour                    | Extinction coefficient of 0 visibility of ten miles or n miles or more for Lake T particles when relative h 70 percent. Method: Be Transmittance through F | nore (0.07 — 30<br>ahoe) due to<br>umidity is less than<br>ta Attenuation and | No<br>Federal<br>Standards         |                                   |  |
| Sulfates                                      | 24 Hour                   | 25 μg/m³   | Ion Chromatography  |                                    |                                   |  |
| Hydrogen<br>Sulfide                           | 1 Hour                    | 0.03 ppm (42 μg/m³)  | Ultraviolet<br>Fluorescence   |                                    |                                   |  |
| Vinyl<br>Chloride <sup>9</sup>                | 24 Hour                   | 0.01 ppm (26 μg/m³)  | Gas<br>Chromatography   |                                    |                                   |  |

See footnotes on next page ...

- 1. California standards for ozone, carbon monoxide (except Lake Tahoe), sulfur dioxide (1 and 24 hour), nitrogen dioxide, suspended particulate matter—PM10, PM2.5, and visibility reducing particles, are values that are not to be exceeded. All others are not to be equaled or exceeded. California ambient air quality standards are listed in the Table of Standards in Section 70200 of Title 17 of the California Code of Regulations.
- 2. National standards (other than ozone, particulate matter, and those based on annual averages or annual arithmetic mean) are not to be exceeded more than once a year. The ozone standard is attained when the fourth highest eight hour concentration in a year, averaged over three years, is equal to or less than the standard. For PM10, the 24 hour standard is attained when the expected number of days per calender year with a 24-hour average concentration above 150 μg/m³ is equal to or less than one. For PM2.5, the 24 hour standard is attained when 98 percent of the daily concentrations, averaged over three years, are equal to or less than the standard. Contact U.S. EPA for further clarification and current federal policies.
- 3. Concentration expressed first in units in which it was promulgated. Equivalent units given in parentheses are based upon a reference temperature of 25°C and a reference pressure of 760 torr. Most measurements of air quality are to be corrected to a reference temperature of 25°C and a reference pressure of 760 torr; ppm in this table refers to ppm by volume, or micromoles of pollutant per mole of gas.
- 4. Any equivalent procedure which can be shown to the satisfaction of the ARB to give equivalent results at or near the level of the air quality standard may be used.
- 5. National Primary Standards: The levels of air quality necessary, with an adequate margin of safety to protect the public health.
- 6. National Secondary Standards: The levels of air quality necessary to protect the public welfare from any known or anticipated adverse effects of a pollutant.
- 7. Reference method as described by the EPA. An "equivalent method" of measurement may be used but must have a "consistent relationship to the reference method" and must be approved by the EPA.
- 8. New federal 8-hour ozone and fine particulate matter standards were promulgated by U.S. EPA on July 18,1997. Contact U.S. EPA for further clarification and current federal policies.
- 9. The ARB has identified lead and vinyl chloride as 'toxic air contaminants' with no threshold level of exposure for adverse health effects determined. These actions allow for the implementation of control measures at levels below the ambient concentrations specified for these pollutants.

California Air Resources Board (5/17/06)